


# CHRYSO® Decap

## Concrete cleaning agent



**CHRYSO® Decap** is a concentrated acid product that disaggregates mortars, concrete and cement laitances.

**CHRYSO® Decap** solubilises binders in these materials, which become uncoated and can be washed off.

**CHRYSO® Decap** contains passivators that prevent any aggression onto metallic surfaces.

### Indicative characteristics

- Nature: liquid
- Colour: Colourless to yellow
- Specific gravity (20 °C): 1,170 ± 0,010
- pH (inferior to): 2,00
- Shelf life: 18 months

### Domains of application

- Superficial laitance suppression
- Suppression of cement stains
- Final cleaning of exposed aggregate concrete surfaces
- Cleaning of coated steel formworks and moulds

### Precautions

Shelf life: 24 months in closed wrapping.

### Method of use

Consumption: between 250 and 400 g/m<sup>2</sup> depending on the desired action depth.

#### Concrete surface cleaning:

Apply a layer of pure product with a brush on the surface to be cleaned. Let the product act (for 10 minutes), and rinse thoroughly with water.

For very low aggression, dilute **CHRYSO® Decap** in 1 or 2 volumes of water.

#### Equipment cleaning:

Dunk the soiled equipment in a bath that contains pure **CHRYSO® Decap** or some diluted in 1 or 2 volumes of water (depending on the desired removal rate).

Leave as such until concrete disaggregates. Once the process has started, pure **CHRYSO® Decap** may be poured in so as to initiate a quick attack. Then add 1 or 2 volumes of water, so as to dilute the solved salts.

### Safety

Before use, refer to the Material Safety Data Sheet.

The MSDS is available on [www.chryso.com](http://www.chryso.com)



The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the «Application» paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Please enquire for the most recent version of the technical data sheet, available on [www.chryso.com](http://www.chryso.com).

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy-les-Moulineaux cedex - FRANCE - Tel.: +33 (0)1 41 17 18 19 - Fax: +33 (0)1 41 17 18 80

