


# CHRYSO® FiniSol Perle

## Concrete Sealer

### Glossy finish



**CHRYSO® FiniSol Perle** is a solvent-based concrete sealer designed to protect aesthetic concrete and to give concrete a wet glossy aspect.

**CHRYSO® FiniSol Perle** is a film-forming sealer that reduces stains and protects against water, oils and dust. It eases natural cleaning of floors.

**CHRYSO® FiniSol Perle** does not yellow the substrate (accelerated ageing test - NF EN ISO 11-507) and shows a good resistance to abrasion and wear (ISO 11-998 and ASTM D24-56).

#### Indicative characteristics

- Nature: liquid
- Colour: Colourless
- Specific gravity (20 °C):  $0,820 \pm 0,050$
- Solid content (halogen):  $22,00\% \pm 2,50\%$
- Flash point: 40 °C
- Shelf life: 12 months

#### Domains of application

- Exposed aggregate concrete
- Street furniture
- Precast elements
- Exposed aggregate roadworks and slabs

#### Precautions

Ensure adequate ventilation when spraying in enclosed areas.

Do not use a thermic spray.

Do not apply this product when the weather is damp or when temperatures are below 10 °C or above 30 °C.

Protect from heat.

The temperature of the substrate must be above 5°C and not exceed 35°C when applying the

product.

#### Method of use

Consumption: 5 to 6 m<sup>2</sup> per litre.

**CHRYSO® FiniSol Perle** is a ready to use product. The dosage of **CHRYSO® FiniSol Perle** depends on the porosity of the surface to be treated. Always do a trial before any application, especially on low porous substrate. Do not use on bricks and clay.

**CHRYSO® FiniSol Perle** can be applied with a brush, a roller or spraying equipment. The surface to be treated must be clean, dry, decarbonated, dust and grease free.

The application of two coats is recommended, with an interval of two to three hours between coats.

It is necessary to wait 21 days before applying onto a new substrate.

The use of a solvent is recommended to clean tools.

#### Safety

Before use, refer to the Material Safety Data Sheet.

The MSDS is available on [www.chryso.com](http://www.chryso.com)



The information contained in this technical data sheet is given to the best of our knowledge and the result from extensive testing - which were conducted in order to remain as objective as possible. However, it cannot, in any case, be considered as a warranty involving our liability in case of misuse or any different use of our products, other than those from the «Application» paragraph of this technical data sheet. Some application tests should be carried out before using the product to ensure that the methods of use and conditions of application of the product are satisfactory. Our technical assistance is at the disposal of the users. Please enquire for the most recent version of the technical data sheet, available on [www.chryso.com](http://www.chryso.com).

CHRYSO S.A.S. - 19 Place de la Résistance - 92446 Issy-les-Moulineaux cedex - FRANCE - Tel.: +33 (0)1 47 18 18 19 - Fax: +33 (0)1 47 18 80

