

CHRYSO®Tard AEP

Set retarding admixture

DESCRIPTION

FIELDS OF APPLICATION

- All cement types
- Hot weather concreting
- Extended workability retention
- Cold joint
- Mass concrete, tile mortar
- Moulded walls
- Piles

INDICATIVE INFORMATION

Product Nature	liquid
Color	Brown
Lifetime	18 months

SPECIFICATIONS

Cl ⁻ Ions content	≤ 0,100 %
Equivalent Content NA ₂ O	≤ 5,00 %
Specific gravity (20°C) in kg/dm ³	1,165 ± 0,010
pH (20°C)	6,00 ± 1,00
Dry Extract (SYNAD - IFSTTAR)	31,00 % ± 1,50

NORMATIVE AND REGULATORY INFORMATION

- This product conforms to NF 085 certification, which technical specifications are those applied in the non harmonised part of NF EN 934-2.
- Adresse AFNOR - 11, Avenue de Pressensé - 93571 Saint Denis La Plaine Cedex
- This product conforms to CE marking. The appropriate declaration can be found on our internet site.

METHOD OF USE

- For other dosages, consult us.
- This product is completely miscible in water.
- This product must be added to the mixing water or at the end of the mixing cycle.
- The optimum dosage of this product can only be established after trial tests, taking into account the rheological characteristics and the required mechanical performances of the concrete.

Dosage :

0.05 to 1.0 kg for 100 kg of cement

PRECAUTIONS

- Protect from frost.
- Avoid prolonged exposure to high temperatures.
- Should the product freeze, it will recover its properties. After thawing, an efficient agitation is necessary until the product is entirely homogeneous again.

SECURITY

Prior to any use, please read carefully the Material Safety Data Sheets.